

株式会社アップルツリー ネオン管一覧

品種	回路電圧 (AC,V)	放電開始電圧 (AC,V)	定格電流 (mA)	直列抵抗 (KΩ)	寿命 (hours)	管径 (mm)	線径 (mm)		
高輝度ランプ									
NE-2HUA(P)LF	100/220	80max	4.5	8.2/33	15000	φ 5.85 × 19	0.45		
準高輝度ランプ									
NE-2Q3(W)LF	100/220	75max	1.7	27/100	20000	φ 5.85 × 15	0.40		
NE-2Q6(W)LF	100/220	70max	1.7	27/100	20000	φ 5.6 × 12	0.40		
NE-2Q7(W)LF	100/220	70max	1.7	30/120	20000	φ 5.85 × 18	0.40		
NL-9C(W)LF	100/220	70max	1.3	33/120	20000	φ 4.85 × 13.5	0.35		
NL-8SC1(W)LF	110/220	70max	1.2	47/150	20000	φ 3.8 × 10	0.35		
標準輝度ランプ									
NL-8S(S)LF	100/	80max	0.3	150/470	20000	φ 3.8 × 11	0.35		
蛍光グローネオンランプ									
品名	発光色	回路電圧 (AC,V)	放電開始電圧 (AC,V)	定格電流 (mA)	直列抵抗 (KΩ)	全光束 (mlm)	寿命 (hours)	寸法2 (mm) typ.	線径 (mm)
NL-33/G(S)LF	Green	100/220	75max	0.7	75/220	15	20000	φ 3.8 × 11	0.35
NL-34/G(W)LF	Green	100/220	75max	1.0	51/180	50	20000	φ 5.85 × 19	0.40
NL-36/G(W)LF	Green	100/220	75max	1.5	30/110	70	20000	φ 5.85 × 18	0.40
NL-41/G(S)LF	Green	100/220	75max	0.8	56/220	30	20000	φ 4.85 × 12	0.35
NL-46/G(W)LF	Green	100/220	75max	1.4	33/120	60	20000	φ 5.85 × 15	0.40